



Cisco 350-001

Exam Name: CCIE Cisco Certified Internetworking Expert

Q & A : 136 Q&As

Pdf Demo

Quality and Value for the 350-001 Exam

[Cert-Inside Practice Exams](#) for Cisco CCIE 350-001 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 350-001 Exam

If you do not pass the CCIE 350-001 exam on your first attempt using our Cert-Inside testing engine, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 350-001 Testing engines and PDF Version

Our CCIE Exam Preparation Material provides you everything you will need to take a [CCIE certification](#) examination. Details are researched and produced by [Cisco Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 350-001 Exams

Exam : Cisco 350-001

Title : CCIE-Routing and Switching Written exam (4.1)

1. Refer to the exhibit. In this network, R1 has been configured to advertise a summary route, 192.168.0.0/22, to R2. R2 has been configured to advertise a summary route, 192.168.0.0/21, to R1. Both routers have been configured to remove the discard route (the route to null created when a summary route is configured) by setting the administrative distance of the discard route to 255.

What will happen if R1 receives a packet destined to 192.168.3.1?

- A. The packet will loop between R1 and R2.
- B. It is not possible to set the administrative distance on a summary to 255.
- C. The packet will be forwarded to R2, where it will be routed to null0.
- D. The packet will be dropped by R1, since there is no route to 192.168.3.1.

Answer: A

2. What is the purpose of an explicit "deny any" statement at the end of an ACL?

- A. none, since it is implicit
- B. to enable Cisco IOS IPS to work properly; however, it is the deny all traffic entry that is actually required
- C. to enable Cisco IOS Firewall to work properly; however, it is the deny all traffic entry that is actually required
- D. to allow the log option to be used to log any matches
- E. to prevent sync flood attacks
- F. to prevent half-opened TCP connections

Answer: D

3. Which two of these are used in the selection of a root bridge in a network utilizing Spanning Tree Protocol IEEE 802.1D? (Choose two.)

- A. Designated Root Cost
- B. bridge ID priority
- C. max age
- D. bridge ID MAC address
- E. Designated Root Priority
- F. forward delay

Answer: BD

4. Two routers configured to run BGP have been connected to a firewall, one on the inside interface and one on the outside interface. BGP has been configured so the two routers should peer, including the correct BGP session endpoint addresses and the correct BGP session hop-count limit (EBGP multihop). What is a good first test to see if BGP will work across the firewall?

- A. Attempt to TELNET from the router connected to the inside of the firewall to the router connected to the outside of the firewall. If telnet works, BGP will work, since telnet and BGP both use TCP to transport data.
- B. Ping from the router connected to the inside interface of the firewall to the router connected to the outside interface of the firewall. If you can ping between them, BGP should work, since BGP uses IP to transport packets.
- C. There is no way to make BGP work across a firewall without special configuration, so there is no simple test that will show you if BGP will work or not, other than trying to start the peering session.
- D. There is no way to make BGP work across a firewall.

Answer: A

5. If a port configured with STP loop guard stops receiving BPDUs, the port will be put into which state?

- A. learning state
- B. listening state
- C. forwarding state
- D. root-inconsistent state

Answer: D

6. The classic Spanning Tree Protocol (802.1D 1998) uses which sequence of variables to determine the best received BPDU?

- A. 1) lowest root bridge id, 2) lowest sender bridge id, 3) lowest port id, 4) lowest root path cost
- B. 1) lowest root path cost, 2) lowest root bridge id, 3) lowest sender bridge id, 4) lowest sender port id
- C. 1) lowest root bridge id, 2) lowest sender bridge id, 3) lowest root path cost 4) lowest sender port id
- D. 1) lowest root bridge id, 2) lowest root path cost, 3) lowest sender bridge id, 4) lowest sender port id

Answer: D

7. When STP UplinkFast is enabled on a switch utilizing the default bridge priority, what will the new bridge priority be changed to?

- A. 8192
- B. 16384
- C. 49152
- D. 65535

Answer: C

8. Spanning Tree Protocol IEEE 802.1s defines the ability to deploy which of these?

- A. one global STP instance for all VLANs
- B. one STP instance for each VLAN
- C. one STP instance per set of VLANs
- D. one STP instance per set of bridges

Answer: C

9. Which of these is mandatory when configuring Cisco IOS Firewall?

- A. Cisco IOS IPS enabled on the untrusted interface
- B. NBAR enabled to perform protocol discovery and deep packet inspection
- C. a route map to define the trusted outgoing traffic

- D. a route map to define the application inspection rules
- E. an inbound extended ACL applied to the untrusted interface

Answer: E

10. Refer to the exhibit. Catalyst R is the root bridge for both VLAN 1 and VLAN 2. What is the easiest way to load-share traffic across both trunks and maintain redundancy in case a link fails, without using any type of EtherChannel link-bundling?

- A. Increase the root bridge priority (increasing the numerical priority number) for VLAN 2 on Catalyst D so that port D2 becomes the root port on Catalyst D for VLAN 2.
- B. Decrease the port priority on R2 for VLAN 2 on Catalyst R so that port D1 will be blocked for VLAN 2 and port D2 will remain blocked for VLAN 1.
- C. Decrease the path cost on R2 on Catalyst R for VLAN 2 so that port D1 will be blocked for VLAN 2 and port D2 will remain blocked for VLAN 1.
- D. Increase the root bridge priority (decreasing the numerical priority number) for VLAN 2 on Catalyst R so that R2 becomes the root port on Catalyst D for VLAN 2.

Answer: B

11. Which three port states are used by RSTP 802.1w? (Choose three.)

- A. Listening
- B. Learning
- C. Forwarding
- D. Blocking
- E. Discarding
- F. Disabled

Answer: BCE

12. Which of these best describes the actions taken when a VTP message is received on a switch configured with the VTP mode "transparent"?

- A. VTP updates are ignored and forwarded out all ports.
- B. VTP updates are ignored and forwarded out trunks only.
- C. VTP updates are made to the VLAN database and are forwarded out trunks only.
- D. VTP updates are ignored and are not forwarded.

Answer: B

13. Which statement correctly describes the disabling of IP TTL propagation in an MPLS network?

- A. The TTL field from the IP packet is copied into the TTL field of the MPLS label header at the ingress edge LSR.
- B. TTL propagation cannot be disabled in an MPLS domain.
- C. TTL propagation is only disabled on the ingress edge LSR.
- D. The TTL field of the MPLS label header is set to 255.
- E. The TTL field of the IP packet is set to 0.

Answer: D

14. What is the purpose of the STP PortFast BPDUGuard feature?

- A. enforce the placement of the root bridge in the network
- B. ensure that a port is transitioned to a forwarding state quickly if a BPDU is received
- C. enforce the borders of an STP domain
- D. ensure that any BPDUs received are forwarded into the STP domain

Answer: C

15. Refer to the exhibit. In this network, R1 is configured not to perform autosummarization within EIGRP. What routes will R3 learn from R2 through EIGRP?

- A. 172.30.1.0/24 and 10.1.2.0/24; EIGRP only performs autosummarization at the edge between two major networks.
- B. 172.30.0.0/16 and 10.1.2.0/24; R2 will perform autosummarization, although R1 will not.
- C. Since R2 is configured without autosummarization, it will not propagate the 172.30.1.0/24 route.
- D. 172.30.0.0/8 and 10.0.0.0/8.

Answer: A

More [350-001 Braindumps](#) Information

Related 350-001 Exams

350-001	350-018	350-030	350-001- LAB	350-029 351-001
---------	---------	---------	-----------------	--------------------

Other Cisco Exams

642-066	642-446	642-053	642-811	646-222
642-652	642-513	350-040	642-983	642-176

350-018-	350-040	350-022	350-024	350-050
LAB	350-020	350-027	350-025	351-018
350-021	350-026	350-023	350-	
			001GB2312-	
			LAB	

650-059	642-481	644-141	640-811	642-979
650-621	650-175	642-821	642-353	642-611