



Cisco 642-825

Exam Name: Implementing Secure Converged Wide Area Networks

Q & A : 119 Q&As

Pdf Demo

Quality and Value for the 642-825 Exam

[Cert-Inside Practice Exams](#) for Cisco CCNP 642-825 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 642-825 Exam

If you do not pass the CCNP 642-825 exam on your first attempt using our Cert-Inside testing engine, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 642-825 Testing engines and PDF Version

Our CCNP Exam Preparation Material provides you everything you will need to take a [CCNP certification](#) examination. Details are researched and produced by [Cisco Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 642-825 Exams

Exam : Cisco 642-825

Title : Implementing Secure Converged Wide Area Networks

1. Refer to the exhibit. On the basis of the information in the exhibit, which two statements are true? (Choose two.)

- A. Any traffic matching signature 1107 will generate an alarm, reset the connection, and be dropped.
- B. Signature 1102 has been modified, but the changes have not been applied to the router.
- C. Signature 1102 has been triggered because of matching traffic.
- D. The Edit IPS window is currently displaying the Global Settings information.
- E. The Edit IPS window is currently displaying the signatures in Details view.
- F. The Edit IPS window is currently displaying the signatures in Summary view.

Answer: BE

2. Refer to the exhibit. Which two statements about the AAA configuration are true? (Choose two.)

- A. A good security practice is to have the none parameter configured as the final method used to ensure that no other authentication

method will be used.

- B. If a TACACS+ server is not available, then a user connecting via the console port would not be able to gain access since no other authentication method has been defined.
- C. If a TACACS+ server is not available, then the user Bob could be able to enter privileged mode as long as the proper enable password is entered.
- D. The aaa new-model command forces the router to override every other authentication method previously configured for the router lines.
- E. To increase security, group radius should be used instead of group tacacs+.
- F. Two authentication options are prescribed by the displayed aaa authentication command.

Answer: DF

3. Refer to the exhibit. Which two statements about the SDF Locations window of the IPS Rule wizard are true? (Choose two.)

- A. An HTTP SDF file location can be specified by clicking the Add button.
- B. If all specified SDF locations fail to load, the signature file that is named default.sdf will be loaded.
- C. The Autosave feature automatically saves the SDF alarms if the router crashes.
- D. The Autosave feature is automatically enabled for the default built-in signature file.
- E. The name of the built-in signature file is default.sdf.
- F. The Use Built-In Signatures (as backup) check box is selected by default.

Answer: AF

4. Refer to the exhibit. On the basis of the partial configuration, which two statements are true? (Choose two.)

- A. A CBAC inspection rule is configured on router RTA.
- B. A named ACL called SDM_LOW is configured on router RTA.
- C. A QoS policy has been applied on interfaces Serial 0/0 and FastEthernet 0/1.
- D. Interface Fa0/0 should be the inside interface and interface Fa0/1 should be the outside interface.
- E. On interface Fa0/0, the ip inspect statement should be incoming.
- F. The interface commands ip inspect SDM_LOW in allow CBAC to monitor multiple protocols.

Answer: AF

5. Refer to the exhibit. On the basis of the information that is provided, which two statements are true? (Choose two.)

- A. An IPS policy can be edited by choosing the Edit button.
- B. Right-clicking on an interface will display a shortcut menu with options to edit an action or to set severity levels.
- C. The Edit IPS window is currently in Global Settings view.
- D. The Edit IPS window is currently in IPS Policies view.
- E. The Edit IPS window is currently in Signatures view.
- F. To enable an IPS policy on an interface, click on the interface and deselect Disable.

Answer: AD

More [642-825 Braindumps](#) Information

Related 642-825 Exams

642-892	642-901	642-825	642-812	642-845
642-801	642-811	642-891	642-746	642-821
642-831	642-902	642-813	642-832	

Other Cisco Exams

646-393	640-801	642-531	642-357	646-002
642-145	642-811	642-436	640-811	646-228
642-979	646-653	642-642	642-964	642-577
642-821	350-050	642-112	350-018-	642-978
			LAB	