



[Cisco 642-845](#)

Exam Name: *Optimizing Converged Cisco Networks*

Q & A : 176 Q&As

Pdf Demo

Quality and Value for the 642-845 Exam

[Cert-Inside Practice Exams](#) for Cisco CCNP 642-845 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 642-845 Exam

If you do not pass the CCNP 642-845 exam on your first attempt using our Cert-Inside testing engine, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 642-845 Testing engines and PDF Version

Our CCNP Exam Preparation Material provides you everything you will need to take a [CCNP certification](#) examination. Details are researched and produced by [Cisco Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 642-845 Exams

Exam : Cisco 642-845

Title : Optimizing Converged Cisco Networks

1. Which two statements are true about the function of CAC? (Choose two.)

- A. CAC provides guaranteed voice quality on a link.
- B. CAC artificially limits the number of concurrent voice calls.
- C. CAC is used to control the amount of bandwidth that is taken by a call on a link.
- D. CAC prevents oversubscription of WAN resources that is caused by too much voice traffic.
- E. CAC allows an unlimited number of voice calls while severely restricting, if necessary, other forms of traffic.
- F. CAC solves voice congestion problems by using QoS to give priority to UDP traffic.

Answer: BD

2. Which two statements are true about the implementation of QoS? (Choose two.)

- A. Implementing DiffServ involves the configuration of RSVP.

- B. Implementing IntServ allows QoS to be performed by configuring only the ingress and egress devices.
- C. Implementing IntServ involves the utilization of RSVP.
- D. Traffic should be classified and marked by the core network devices.
- E. Traffic should be classified and marked as close to the edge of the network as possible.

Answer: CE

3. Which two QoS statements are true about the use of the SDM QoS wizard? (Choose two.)

- A. Business-critical traffic includes VoIP and voice signaling packets.
- B. SDM can be used to configure a basic QoS policy for incoming traffic on WAN interfaces and IPsec tunnels.
- C. SDM can provide QoS for real-time traffic and business-critical traffic.
- D. SDM creates a custom-queuing (CQ) or a priority-queuing (PQ) policy.
- E. SDM creates a low latency queuing (LLQ) service policy with its associated classes.
- F. When allocating bandwidth, values can be entered in either bandwidth percentage or kilobytes per second (kBps).

Answer: CE

4. What are the steps for configuring stateful NBAR for dynamic protocols?

- A. Use the command `ip nbar protocol-discovery` to allow identification of stateful protocols. Use the command `ip nbar port-map` to attach the protocols to an interface.
- B. Use the command `match protocol rtp` to allow identification of real-time audio and video traffic. Use the command `ip nbar port-map` to extend the NBAR functionality for well-known protocols to new port numbers.
- C. Use the command `match protocol` to allow identification of stateful protocols. Use the command `ip nbar port-map` to attach the protocols to an interface.
- D. Configure a traffic class. Configure a traffic policy. Attach the traffic policy to an interface.
- E. Configure video streaming. Configure audio streaming. Attach the codec to an interface.

Answer: D

5. Voice activity detection (VAD) suppresses the transmission of silence patterns. On average, and assuming that a link carries at least 24 calls, what percentage of total bandwidth could VAD save?

- A. 5
- B. 15
- C. 25
- D. 35
- E. 45
- F. 55

Answer: D

6. Which two Cisco AutoQoS interface statements are true? (Choose two.)

- A. AutoQoS is supported on Frame Relay multipoint subinterfaces.
- B. AutoQoS is supported on low-speed ATM PVCs in point-to-point subinterfaces.
- C. AutoQoS is supported on serial PPP and HDLC interfaces.
- D. AutoQoS is supported only on Frame Relay main interfaces and not on any subinterface configuration.

Answer: BC

7. Which two wireless security statements are true? (Choose two.)

- A. A TACACS+ server is required to implement 802.1x.
- B. MIC protects against man-in-the-middle and replay attacks.
- C. The 802.1x standard provides encryption services for wireless clients.
- D. The AES (symmetric block cipher) is specified in the IEEE 802.11i specification.
- E. The IEEE 802.11i specification uses RC4 as its encryption mechanism.
- F. WPA requires TKIP and AES as encryption methods.

Answer: BD

8. Which codec standard would provide the highest voice-quality, mean opinion score (MOS)?

- A. G.711, PCM
- B. G.728, LDCELP
- C. G.729, CS-ACELP
- D. G.729A, CS-ACELP

Answer: A

9. Which two statements regarding the Wireless LAN Solution Engine (WLSE) are true? (Choose two.)

- A. To support fault and policy reporting, the WLSE requires a Wireless Control System (WCS).

- B. When WLSE detects an AP failure, it automatically increases the power and cell coverage of nearby APs.
- C. WLSE requires the 2700 location appliance to offer location tracking.
- D. WLSE can locate rogue APs and automatically shut them down.
- E. WLSE configuration is done using the command line interface (CLI) or a WEB based template.

Answer: BD

10. Which three configuration tasks are required to successfully deploy NBAR to recognize TCP and UDP stateful protocols? (Choose three.)

- A. Over leased lines, use the multilink ppp command to reduce latency and jitter, and to create Distributed Link Fragmentation and interleaving.
- B. Use the service-policy command to attach a traffic flow to an interface on the router.
- C. Use the ip rsvp bandwidth command to set a strict upper limit on the bandwidth NBAR uses, and to guarantee admission of any flows.
- D. Use the policy-map command to define one or more QoS policies (such as shaping, policing, and so on) to apply to traffic defined by a class map.
- E. Use the random-detect dscp command to modify the default minimum and maximum thresholds for the DSCP value.
- F. Use the class-map command to define one or more traffic classes by specifying the criteria by which traffic is classified.

Answer: BDF

More [642-845 Braindumps](#) Information

Related 642-845 Exams

642-892	642-901	642-825	642-812	642-845
642-801	642-811	642-891	642-746	642-821
642-831	642-902	642-813	642-832	

Other Cisco Exams

350-024	642-661	642-511	642-552	642-382
642-381	640-460	646-301	642-372	650-180
642-811	642-524	642-892	646-046	646-391
642-425	646-151	642-551	642-741	642-983